



**A2L**

**SILENCIADORES DE DESCARGA**

Presión de servicio : 46 bar



MODELO	Conexion Soldar	Potencia Frigorífica (Kw)			Dimensiones		€/und	CODIGO
		R22	R134a	R404A	Diam (mm)	L (mm)		
<b>SCY 30</b>	3/8"	7,0	5,5	8,0	53	162,5	<b>87,70</b>	CT32500
<b>SCY 40</b>	1/2"	11,5	9,0	14,0	53	162,5	<b>89,10</b>	CT32501
<b>SCY 50</b>	5/8"	19,0	15,0	22,5	53	166,5	<b>95,10</b>	CT32502
<b>SCY 60</b>	3/4"	27,5	21,5	32,5	93	163,0	<b>131,00</b>	CT32503
<b>SCY 70</b>	7/8"	38,5	30,0	45,5	93	183,0	<b>133,00</b>	CT32504
<b>SCY 90</b>	1 1/8"	60,0	47,0	71,0	93	283,0	<b>150,00</b>	CT32505
<b>SCY 110</b>	1 3/8"	94,0	73,5	111,0	93	303,0	<b>187,00</b>	CT32506
<b>SCY 130</b>	1 5/8"	134,0	105,0	160,0	93	303,0	<b>224,00</b>	CT32507
<b>SCY 170</b>	2 1/8"	229,0	179,5	273,5	127	681,0	<b>562,00</b>	CT32508
<b>SCY 210</b>	2 5/8"	350,5	274,5	418,5	156	620,6	<b>1.020,00</b>	CT32509
<b>SCY 250</b>	3 1/8"	497,5	390,0	594,5	156	837,0	<b>1.200,00</b>	CT32510

**SILENCIADORES DE DESCARGA SDS**



Montaje en posición vertical y horizontal. Para unos mejores resultados, instalar antes del silenciador de descarga un eliminador de vibraciones

Presión de servicio : 42 bar.



MODELO	Conexion Soldar	Capacidad (W)	TONS	Dimensiones		€/und	CODIGO
				Diam (mm)	L (mm)		
<b>SDS-500</b>	3/8"	7.000	2	50,8	189	<b>37,70</b>	21.001
<b>SDS-600</b>	1/2"	10.500	3	50,8	189	<b>49,90</b>	21.002
<b>SDS-700</b>	5/8"	17.500	5	50,8	189	<b>59,10</b>	21.003
<b>SDS-900</b>	7/8"	25.700 a 35.200	7,5 a 10	76,2	229	<b>73,40</b>	21.005
<b>SDS-1000</b>	1 1/8"	352.00 a 53.100	10 a 15	76,2	235	<b>Consultar</b>	21.006
<b>SDS-1100</b>	1 3/8"	53.100 a 87.800	15 a 25	76,2	349	<b>Consultar</b>	21.007
<b>SDS-1200</b>	1 5/8"	87.800 a 175.000	25 a 50	101,6	406	<b>Consultar</b>	21.008