

COMPRESORES DE DOS ETAPAS DORIN SERIE 2S.



MODELO	Desplazamiento Baja/Alta presión	Nº Cilindros Baja/Alta presión
2S-H1200L / 2S-H1500	56,49 / 37,91 m3/h	2 / 2
2S-H1500L / 2S-H2000	75,83 / 37,91 m3/h	4 / 2
2S-H2000L / 2S-H2500	85,01 / 42,51 m3/h	4 / 2
2S-H2500L/2S-H3000	102,35 / 51,17 m3/h	4 / 2
2S-H3000L / 2S-H3500	112,97 / 56,49 m3/h	4 / 2
2S-H3200L / 2S-H4000L	122,39 / 61,19 m3/h	4 / 2

DOBLE ETAPA (SUBENFRIADOR DE LIQUIDO incluido con el precio)

R404A/R449A

Rdtos expresados para R404A

MODELO	Temp. Cond. (°C)	Potencia frigorífica en vatios (Con subenfriador de líquido) a temp. evap.							€/Und	CÓDIGO
		-30°C	-35°C	-40°C	-45°C	-50°C	-55°C	-60°C		
2S-H1200L	+30°C	-	-	13.720	11.000	8.690	6.750	5.140	8.850,00	2SH1200L
	+50°C	-	-	12.830	10.270	8.080	6.250	-		
2S-H1500	+30°C	20.560	16.890	13.720	11.000	8.690	6.750	-	9.430,00	2SH1500
	+50°C	19.240	15.810	12.830	10.270	8.080	6.250	-		
2S-H1500L	+30°C	-	-	18.710	15.020	11.880	9.240	7.060	10.800,00	2SH1500L
	+50°C	-	-	17.490	14.020	11.060	8.580	-		
2S-H2000	+30°C	27.950	23.000	18.710	15.020	11.880	9.240	-	11.300,00	2SH2000
	+50°C	26.120	21.510	17.490	14.020	11.060	8.580	-		
2S-H2000L	+30°C	-	-	20.790	16.690	13.200	10.270	7.840	11.900,00	2SH2000L
	+50°C	-	-	19.430	15.580	12.280	9.520	-		
2S-H2500	+30°C	31.060	25.560	20.790	16.690	13.200	10.270	-	12.500,00	2SH2500
	+50°C	29.030	23.900	19.430	15.580	12.280	9.520	-		
2S-H2500L	+30°C	-	-	24.750	19.860	15.700	12.200	9.300	13.500,00	2SH2500L
	+50°C	-	-	23.110	18.510	14.590	11.300	-		
2S-H3000	+30°C	37.000	30.440	24.750	19.860	15.700	12.200	-	14.400,00	2SH3000
	+50°C	34.550	28.440	23.110	18.510	14.590	11.300	-		
2S-H3000L	+30°C	-	-	27.040	21.700	17.150	13.320	10.160	15.400,00	2SH3000L
	+50°C	-	-	25.250	20.220	15.930	12.330	-		
2S-H3500	+30°C	40.430	33.260	27.040	21.700	17.150	13.320	-	16.300,00	2SH3500
	+50°C	37.750	31.070	25.250	20.220	15.930	12.330	-		
2S-H3200L	+30°C	-	-	28.980	23.240	18.360	14.260	10.860	17.300,00	2SH3200L
	+50°C	-	-	27.030	21.630	17.040	13.180	-		
2S-H4000	+30°C	43.340	35.650	28.980	23.240	18.360	14.260	-	18.300,00	2SH4000
	+50°C	40.450	33.280	27.030	21.630	17.040	13.180	-		

Accesorio : Resistencia de cárter : Consultar