

VÁLVULAS DE SEGURIDAD Y DE 3 VÍAS.



Válvulas de seguridad angulares para NH3



MPO: 40 bar

Rango de temperatura: -50°C a +100°C.

Acción directa dependiente de la presión de salida

Modelo	Presión tarado Bar	Entrada	Salida	€/Und.	CÓDIGO
SFA 10 T 210	10	G 1/2"	G 3/4"	388,00	148F4210
SFA 10 T 213	13	G 1/2"	G 3/4"	388,00	148F4213
SFA 10 T 216	16	G 1/2"	G 3/4"	388,00	148F4216
SFA 10 T 218	18	G 1/2"	G 3/4"	388,00	148F4218
SFA 10 T 221	21	G 1/2"	G 3/4"	388,00	148F4221
SFA 15 T 210	10	G 3/4"	G 1"	518,00	148F3210
SFA 15 T 213	13	G 3/4"	G 1"	518,00	148F3213
SFA 15 T 216	16	G 3/4"	G 1"	518,00	148F3216
SFA 15 T 218	18	G 3/4"	G 1"	518,00	148F3218
SFA 15 T 221	21	G 3/4"	G 1"	518,00	148F3221

Válvula de 3 vías



Incluye racores a roscar para SFA

Modelo	Kv (m ³ /h)	Entrada	Valvula compatible	€/Und.	CÓDIGO
DSV 10 ND20	5,5	DIN 15 (roscar)	SFA 10 T	666,00	148F3054
DSV 1 ND20	17,5	DIN 25 (soldar)	SFA 15 T	1.060,00	148F3005